



AW-5600AT

Fully Integrated Weigh-Wrap-Label System



PC Based

- PC based (*Linux*)
- 12.1" Full Color Touch Screen
- 300 DPI Thermal Head
- Linerless Labeling Capabilities
- Small Foot Print

New Brunswick International, Inc.
DIGI Retail Scale and Labeling Systems

POP Labeler

Twin Labeler

Bottom Labeler



Easy Film Change

Specifications

Operating System.....Linux

Memory.....8.8GB

General

Power source 208/240v; 3 Phase; 50/60Hz; 2.7kVA

power consumption 220-240V; 1Ø; 50/60Hz; 7.5A; 1.7kW

Dimensions 1410/55.5(W) x 1535/60.4(D) x 1465/57.7(H) mm/inches

Net Weight Approx. 400 kg/882 lb (Single Labeler Type)

Operation humidity 90% RH (max.) with no condensation

Wrapping

Package Size Width: 130-380 mm (5.1-15 inches)
Height: 10-130 mm (0.4– 5.1 inches)
Depth: 80-254 mm (3.1-10 inches)

Wrapping Speed Max. 36 packages/min.

Number of film roll One Roll

Film Width 300-450 mm (12-18 inches)

Film Length Max. 1,500 m (4,900 feet)

Printer and Labeler

Type Thermal Printer

Dot Density 12 dot/mm (300 dpi)

Printing Width 40-80 mm (1.6 –3.1 inches)

Printing Length 28-105 mm (1.1-4.1 inches)

Label Size Width: 40-80 mm (1.6-3.1 inches)
Length: 28-105 mm (1.1-4.1 inches)

Label roll diameter Max. 210 mm (8.2 inches)

Label roll core diameter 76 mm (3.0 inches)



New Brunswick International, Inc.

Corporate Headquarters
76 Veronica Ave
Somerset, NJ 08873
TEL: (732) 828-3633
FAX: (732) 828-4884

West Coast Office
530 West Central Ave. Suite C
Brea, CA 92821
TEL: (714) 671-7911
Fax: (714) 671-0798

